



4000/5000 SERIES

SR Range



Compact, durable & versatile

The 4000 & 5000 Series hose reels are durable and compact and used for a wide variety of applications where space requirements are critical. A full flow shaft and swivel assembly assures maximum product delivery. The standard low pressure hose reel is for air or water service only. The medium and high pressure reels are for oil and grease respectively.

Consult Reelcare if you are unsure of your application, the sales department are there to help and will be more than happy to advise.



MODELS	I.D.		O.D.	LENGTH		PRESSURE		CONNECTION		WEIGHT	MODELS	PRESSURE		WEIGHT	
	with hose	mm		inch	mm	m	ft	Bar	PSI			inlet	outlet		with hose
4000 Low Pressure Air & Water															
4420 OLP118	6	1/4	13	6	20	21	300	3/8	1/4	9	4400 OLP118	35	500	8	
4425 OLP118	6	1/4	13	7.5	25	21	300	3/8	1/4	9	4400 OLP118	35	500	8	
4435 OLP118	6	1/4	13	11	35	21	300	3/8	1/4	10	4400 OLP118	35	500	8	
4617 OLP118	10	3/8	16	5	17	21	300	3/8	1/4	9	4600 OLP118	35	500	8	
4625 OLP118	10	3/8	16	8	25	21	300	3/8	1/4	9	4600 OLP118	35	500	8	
5000 Low Pressure Air & Water															
5450 OLP118	6	1/4	14	15	50	21	300	3/8	1/4	12	5400 OLP118	35	500	9	
5635 OLP118	10	3/8	16	11	35	21	300	3/8	1/4	11	5600 OLP118	35	500	10	
A5825 OLP118	12	1/2	20	8	25	21	300	3/8	1/2	14	A5800 OLP118	35	500	10	
5000 Medium Pressure Air, Water & Oil															
5435 OMP118	6	1/4	15	11	35	190	2750	3/8	1/4	14	5400 OMP118	207	3000	20	
5630 OMP118	10	3/8	20	9	30	155	2250	3/8	3/8	14	5600 OMP118	207	3000	21	
5000 High Pressure Grease															
5430 OHP118	6	1/4	15	9	30	345	5000	1/4	1/4	14	5400 OHP118	345	5000	12	
5625 OHP118	10	3/8	20	7.5	25	276	4000	1/4	1/4	14	5600 OHP118	345	5000	12	
DIMENSIONS 4000 W 136 mm L 321 mm H 327 mm															
DIMENSIONS 5000 W 152 mm L 343 mm H 368 mm															

Also available for welding pg32, twin hydraulic pg33, cable pg26 and in stainless steel pg24