



GEN III SERIES

SG Range



Corrosion proof composite material

The GEN III is a durable yet economical reel, lightweight and easy to operate. The GEN III has been designed to meet the harsh demands of industrial environments and is manufactured from corrosion proof, composite materials for continuous, trouble-free operation.



FEATURES & BENEFITS

High Quality Finished Edge Spring

The GEN III boasts a high quality roll formed drive spring which virtually eliminates the possibility of drive spring failure due to micro cracks which occur on standard slit edge drive springs used on many hose reels.

Full Flow Heavy Duty Swivel

The heavy duty swivel reduces possible cracking in freezing conditions and allows us to offer full flow fluid paths for maximum media flow rates.

Multi Position Locking Mechanism

The GEN III has a unique multi position locking mechanism that provides a complete, positive retraction every time.

Composite Materials

The GEN III is manufactured from tough, impact & corrosion resistant UV stabilised polypropylene with added anti-static and flame retardants.

MODELS	I.D.		LENGTH		PRESSURE		CONNECTION		WEIGHT	
	with hose	mm	inch	m	ft	Bar	PSI	inlet		outlet
Low Pressure Air & Water										
AW815-001		8	5/16	15	50	17	240	3/8"	3/8"	11Kg
AW820-001		8	5/16	20	66	17	240	3/8"	3/8"	12Kg
AW1015-001		10	3/8	15	50	17	240	3/8"	3/8"	12Kg
AW1020-001		10	3/8	20	20	17	240	3/8"	3/8"	12Kg
AW1215-001		12	1/2	15	50	17	240	1/2"	1/2"	12Kg
AW1218-001		12	1/2	18	60	17	240	1/2"	1/2"	12Kg
DIMENSIONS SG RANGE W 239 mm L 559 mm H 490 mm										

See page 32 for oxy/acetylene reels