

560 | SE Range

Large Capacity

The 560 is a large capacity series of hose reels for long lengths of hose. The 560 Series is an extremely durable range of high quality steel hose reels that will suit hose sizes ranging from 10mm id (3/8") up to 25mm id (1"). With its sturdy design, the 560 Series allows the user to manage hose safely, practically and effectively. The SE Range is available with or without hose and is suitable for numerous applications including: air, water, oils and fuels.

Consult Reelcare if you are unsure of your application, the sales department are there to help and will be more than happy to advise.

Full Flow Swivels

Available in: Brass, steel, stainless steel AISI 304.
Available with PU, Viton, or Teflon seals.

Adjustable Guide Arm

Allows wall, floor and ceiling mounting.

Easy Installation


Reel comes with a mounting template.

Powder Coated Steel

Reduces the risk of corrosion.

Enclosed drive spring

Completely enclosed drive spring built into the reel.



| MODELS with hose | MODELS without hose | I.D. | | O.D. mm | LENGTH | | PRESSURE | | CONNECTION | | WEIGHT with hose |
|---------------------|------------------------|------|------|------------|--------|----|----------|-----|------------|--------|---------------------|
| | | mm | inch | | m | ft | Bar | PSI | inlet | outlet | |

Low Pressure Air & Water

| | | | | | | | | | | | |
|----------|----------|---------|---------|---------|----|-----|----|-----|---|-----|----|
| | SE560-10 | 19 & 25 | 3/4 & 1 | 25 & 32 | 30 | 100 | 20 | 300 | 1 | 1 | 30 |
| SE560-11 | | 19 | 3/4 | 25 | 30 | 100 | 20 | 300 | 1 | 3/4 | 50 |
| SE560-15 | | 25 | 1 | 32 | 30 | 100 | 20 | 300 | 1 | 1 | 60 |

Medium Pressure Hot Water 130°C

| | | | | | | | | | | | |
|----------|----------|---------|---------|---------|----|-----|-----|------|---|-----|----|
| | SE560-20 | 19 & 25 | 3/4 & 1 | 25 & 32 | 30 | 100 | 100 | 1500 | 1 | 1 | 30 |
| SE560-21 | | 19 | 3/4 | 25 | 30 | 100 | 100 | 1500 | 1 | 3/4 | 55 |
| SE560-25 | | 25 | 1 | 32 | 30 | 100 | 100 | 1500 | 1 | 1 | 60 |

High Pressure Hot Water 130°C

| | | | | | | | | | | | |
|----------|----------|----|-----|----|----|-----|-----|------|-----|-----|----|
| | SE560-30 | 10 | 3/8 | 18 | 50 | 165 | 200 | 3000 | 3/8 | 1/2 | 30 |
| SE560-32 | | 10 | 3/8 | 18 | 50 | 165 | 200 | 3000 | 3/8 | 3/8 | 75 |

DIMENSIONS 560 W 488 mm L 578 mm H 522 mm



440

SE Range

Enclosed

The 440 Series are fully enclosed hose reels. This series is ideal for the lubrication and automotive industries. The 440 Series is extremely durable and will suit hose sizes ranging from 6mm id (1/4") up to 12mm id (1/2"). The 440 Series allows the user to manage hose safely, practically and effectively. They are available with or without hose and are suitable for applications including: air, water, oils and grease.

Consult Reelcare if you are unsure; the sales department are there to help and will be more than happy to advise.

Fully Enclosed

Excellent for workshops and garages

Full Flow Swivels


Allows maximum product delivery

Powder Coated Steel

Reduces the risk of corrosion.

Enclosed drive spring

Completely enclosed drive spring built into the reel.



| MODELS with hose | MODELS without hose | I.D. | | O.D. | | LENGTH | | PRESSURE | | CONNECTION | | WEIGHT |
|------------------|---------------------|------|------|------|----|--------|----|----------|-----|------------|--------|-----------|
| | | mm | inch | mm | mm | m | ft | Bar | PSI | inlet | outlet | with hose |

Low Pressure Air & Water

| | | | | | | | | | | | |
|----------|----------|---------|-----------|---------|---------|---------|----|-----|-----|-----|----|
| | SE440-10 | 10 & 12 | 3/8 & 1/2 | 17 & 22 | 18 & 15 | 60 & 50 | 20 | 300 | 1/2 | 1/2 | 21 |
| SE440-11 | | 12 | 1/2 | 22 | 15 | 50 | 20 | 300 | 1/2 | 1/2 | 24 |
| SE440-12 | | 10 | 3/8 | 17 | 12 | 40 | 20 | 300 | 1/2 | 3/8 | 24 |
| SE440-13 | | 10 | 3/8 | 17 | 18 | 60 | 20 | 300 | 1/2 | 3/8 | 25 |

Medium Pressure Oil, Coolant & Allied Products

| | | | | | | | | | | | |
|----------|----------|----|-----|----|----|----|-----|------|-----|-----|----|
| | SE440-40 | 12 | 1/2 | 22 | 15 | 50 | 150 | 2000 | 1/2 | 1/2 | 21 |
| SE440-41 | | 12 | 1/2 | 22 | 10 | 33 | 150 | 2000 | 1/2 | 1/2 | 25 |
| SE440-42 | | 12 | 1/2 | 22 | 15 | 50 | 150 | 2000 | 1/2 | 1/2 | 27 |

High Pressure Grease Reels

| | | | | | | | | | | | |
|----------|----------|--------|-----------|---------|---------|---------|-----|------|-----|-----|----|
| | SE440-50 | 6 & 10 | 1/4 & 3/8 | 14 & 17 | 18 & 15 | 60 & 50 | 600 | 9000 | 3/8 | 1/2 | 21 |
| SE440-51 | | 6 | 1/4 | 14 | 12 | 40 | 600 | 9000 | 3/8 | 1/4 | 28 |
| SE440-52 | | 6 | 1/4 | 14 | 18 | 60 | 600 | 9000 | 3/8 | 1/4 | 29 |
| SE440-55 | | 10 | 3/8 | 17 | 10 | 33 | 600 | 9000 | 3/8 | 1/4 | 28 |

DIMENSIONS 440 W 217 mm L 500 mm H 485 mm