



# STAINLESS STEEL

## SR Range

### Corrosion Resistant

Reelcare's range of high quality stainless steel hose reels will increase the life of expensive wash down, chemical, and fluid transfer hoses. By properly storing your hose on Reelcare's range of stainless steel hose reels, you will be reducing the risk of tripping accidents caused by improper hose handling. Stainless steel hose reels are ideal for food processing, pre-rinse, wash down, chemical transfer and industrial solvent handling. They are also suitable for coastal, offshore oil industry, on-board ship and other marine applications where the harsh environment of salt water spray requires the use of stainless steel hose reels.



MODELS	I.D.		O.D.		LENGTH		PRESSURE		CONNECTION	APPROX WGT	DIMENSIONS		
	without hose	mm	inch	m	m	ft	Bar	PSI	inlet	without hose	W	L	H
<b>Spring Rewind - Low Pressure Stainless Steel</b>													
5600 OLS70	10	3/8	19	11	35	35	500	3/8	10	152	348	368	
7800 OLS70	12	1/2	21	15	50	35	500	1/2	20	178	483	514	
81000 OLS70	10	3/8	19	30	100	35	500	1/2	20	267	610	645	
82000 OLS70	12	1/2	21	30	100	35	500	1/2	36	267	610	645	
83000 OLS70	19	3/4	31	15	50	35	500	3/4	52	267	610	645	
D83000 OLS70	19	3/4	31	23	75	35	500	3/4	34	362	613	645	
D84000 OLS70	25	1	35	15	50	35	500	1	54	362	613	645	
D9200 OLS70	12	1/2	21	30	100	35	500	1/2	34	400	667	667	
D9300 OLS70	19	3/4	31	23	75	35	500	3/4	35	400	667	667	
D9400 OLS70	25	1	35	15	50	35	500	1	53	400	667	667	
<b>Spring Rewind - Medium Pressure Stainless Steel</b>													
5600 OMS70	10	3/8	19	10	30	210	3000	3/8	10	152	348	368	
7600 OMS55	10	3/8	19	18	60	210	3000	3/8	19	178	483	514	
7800 OMS70	12	1/2	22	15	50	210	3000	1/2	21	178	483	514	
82000 OMS70	12	1/2	22	23	75	103	1500	1/2	37	267	610	645	
83000 OMS70	19	3/4	32	15	50	103	1500	3/4	37	267	610	645	
D9300 OMS70	19	3/4	32	15	50	210	3000	1/2	54	400	667	667	
<b>Manual Rewind - Medium &amp; Low Pressure Stainless Steel</b>													
HS18000M	12	1/2	22	60	200	210	3000	1/2	15	318	508	483	
HS28000M	12	1/2	22	90	300	210	3000	1/2	16	394	508	483	
HS19000M	19	3/4	30	23	75	210	3000	3/4	16	318	508	483	
HS29000M	19	3/4	30	38	125	210	3000	3/4	17	394	508	483	
HS37000L70	25	1	38	30	100	35	500	1	21	572	534	530	



# STAINLESS STEEL

## SE Range

MODELS	I.D.		O.D.	LENGTH		CONNECTION		WEIGHT	MODEL	APPROX WGT	DIMENSIONS			
	with hose	mm		inch	mm	m	ft				inlet	outlet	with hose	without hose
<b>Low Pressure Air &amp; Cold Water - 20 Bar</b>														
SE302-11		10	3/8	16	12	40	3/8	3/8	10	SE302-10	8	186	340	300
SE302-13		10	3/8	12	18	60	3/8	1/4	11			186	340	300
SE352-11		10	3/8	16	18	60	3/8	3/8	12	SE352-10	12	186	390	380
SE352-12		10	3/8	15	20	66	3/8	3/8	15			186	390	380
SE432-11		12	1/2	20	15	50	1/2	1/2	19	SE432-10	14	186	460	450
SE432-13		12	1/2	16	18	60	1/2	3/8	21			186	460	450
SE532-11		12	1/2	20	20	66	1/2	1/2	30	SE532-10	19	203	560	550
SE532-12		12	1/2	20	25	80	1/2	1/2	35			203	560	550
SE542-12		19	3/4	25	20	66	1/2	3/4	35	SE542-10	24	300	560	550
SE542-13		25	1	32	15	50	1/2	1	40			300	560	550
SE562-11		19	3/4	32	30	100	1	3/4	65	SE562-10	30	488	578	522
SE562-15		25	1	35	30	100	1	1	70			488	578	522
<b>Hot Water 130 °C Medium Pressure - 100 Bar</b>														
SE302-41		12	1/2	20.5	8	25	1/2	1/2	12	SE302-40	8	186	340	300
SE302-42		10	3/8	17	12	40	1/2	1/2	13			186	340	300
SE352-41		12	1/2	21	10	35	1/2	1/2	13	SE352-40	10	186	390	380
SE352-42		10	3/8	17	17	65	1/2	1/2	16			186	390	380
SE432-21		12	1/2	18	10	35	1/2	1/2	21	SE434-20	14	186	460	450
SE432-22		12	1/2	18	15	50	1/2	1/2	23			186	460	450
SE532-21		12	1/2	21	20	66	1/2	1/2	30	SE534-20	26	205	560	550
SE532-20		12	1/2	21	25	80	1/2	1/2	32					
SE544-22		19	3/4	25	15	50	1	3/4	38	SE544-20	24	300	560	550
SE544-23		25	1	31	15	50	1	1	38			300	560	550
SE564-23		19	3/4	25	40	130	1	3/4	68	SE564-20	30	488	578	522
SE564-25		25	1	31	30	100	1	1	72			488	578	522
<b>Hot Water 130 °C High Pressure - 200 Bar</b>														
SE432-31		10	3/8	17	12	40	3/8	3/8	20	SE432-30	14	186	460	450
SE432-32		10	3/8	17	18	60	3/8	3/8	23			186	460	450
SE532-31		10	3/8	17	25	80	3/8	3/8	38	SE532-30	24	203	560	550
SE532-32		10	3/8	17	20	66	3/8	3/8	36			203	560	550
SE542-31		10	3/8	17	30	100	3/8	3/8	45	SE544-30	25	300	560	550
SE562-31		10	3/8	17	40	130	3/8	3/8	70	SE562-30	38	488	578	522
SE562-32		10	3/8	17	50	160	3/8	3/8	75			488	578	522