



SRN Range

Custom Reels

Working from a base reel the following models can be configured to meet you exact requirements

1010 Series

1/2", 3/4" or 1" Fluid Path

REWIND: Direct crank rewind or motor driven. AC or DC electric, air or hydraulic motor.

Pin lock assembly is optional on manual rewind reels.

INLET: 1/2" - 1" female/male NPT 90° swivel joint. Straight inlet available as an additional accessory.

GOOSENECK: 1/2" up to 1" female/male NPT. Other sizes and/or threads available if specified.



2400 Series

1/2", 3/4" or 1" Fluid Path

REWIND: Gear-drive crank rewind or motor driven. AC or DC electric, air or hydraulic motor.

Pin lock assembly is optional on manual rewind reels.

INLET: 1/2" - 1" female/male NPT 90° swivel joint. Straight inlet available as an additional accessory

GOOSENECK: 1/2" up to 1" female/male NPT. Other sizes and/or threads available if specified.



3700 Series

2" Fluid Path

REWIND: Gear-drive crank rewind or chain and sprocket drive powered by A.C. or D.C. electric motor, compressed air motor or hydraulic motor.

INLET: 2" male NPT straight swivel joint is standard. 90° Inlet available if required

GOOSENECK: 2" female/male NPT. Other sizes and/or threads available if specified.





SRN Range

Custom Reels

3800 Series for Petroleum Service

1½ or 2" Fluid Path

REWIND: 30° crank rewind assembly or motor driven. AC or DC electric, air or hydraulic motor.

INLET: 90° is standard., straight swivel joint can be specified if required.

GOOSENECK: 1¼", 1½" or 2" female/male NPT is available.



3900 Series

1½" Fluid Path

REWIND: Gear-drive crank rewind or motor driven. AC or DC electric, air or hydraulic motor.

Pin lock assembly is optional on manual rewind reels.

INLET: 1½" female NPT straight swivel joint is standard. 90° Inlet available if required

GOOSENECK: 1", 1¼" and 1½" female/male NPT outlet. Other sizes and/or threads available if specified.



5900 Series

3" or 4" Fluid Path

REWIND: Gear-drive crank rewind or motor driven. AC or DC electric, air or hydraulic motor.

INLET: 3" straight is standard. 90° available if required.

GOOSENECK: 3" female NPT. Other sizes and/or threads available if specified.

NOTE: 4" 90° inlet & 4" female NPT gooseneck 24" drum diameter is standard on 4" reels.

